



### Rich Interface

- Virtual serial port for USB connection
- USB+Serial+Ethernet
- Parallel+USB

### HIGH PRINT SPEED (300mm/sec) INTEGRATED MECHANISM



#### Integration of mechanism and cutter

150km mechanism lifespan;  
1,500,000 times cutter lifespan

### Thermal Receipt Printer

INNOVATION, QUALITY

NEW PACKING, A NEW IMAGE



### Specification

Print method	Direct thermal
Print speed	300mm/sec.
Paper width	79.5 ± 0.5mm
Print width	64/72mm
Interface	USB+Serial+Ethernet、Parallel+USB
Wall mount	Support
Power	DC24V/2A
Reliability	150km mechanism lifespan; 1,500,000 times cutter lifespan
Weight	1.23kg
Dimension	180.6X139X127MM(LXWXH)

# NEW SIMPLE. BETTER. FASTER Thermal Receipt Printer



Support 2D Barcode Printing  
Integration of mechanism and cutter  
300mm/sec ultra high speed

- Compatible with ESC/POS and Star commands
- Waterproof, oil-proof, dust-proof structure
- Kitchen printing and network printing supported
- Network status monitoring, multilink printing supported
- OPOS driver supported
- Printer authentication and software bundle
- High speed driver printing mode, serial port speed is 66% faster
- Auto print recovering when network disconnected
- Virtual serial port for USB connection, USB port supports OPOS application
- 100MB network interface card makes the connection and print much faster, stop receipts misprinting